

SCHÖNE

Lighting





SCHÖNE lighting will complete your lighting needs by combining **Quality** and **economical** together to ensure a wonderful experience every time at home or at work.

Schöne Lighting

Product Information

Who Are "We"

Schöne Lighting is a part of Luminance System's wings', which its product line and focus are solely on Residential and Commercial Lighting. We differentiate ourselves from others by delivering Quality product without Premium Pricing. We always strive to make our product a step ahead from others so what we can exceed your expectations.

Benefit

Saving money



Reduce your lighting utility bills, thus saving you money.

Comfortable



Your "Comfortability is our Priority". We try to bring something extraordinary in your daily life by using our product.

Efficient Energy



Wastage of energy can cause you money. Thus have Efficient Energy is crucial in your daily life

Reliability



By increasing the reliability of our product, user can now enjoy a longer lifespan lighting product with a peace of mind.

Power Factor



High power factor can improve the power quality in a building's electrical system. Furthermore, upgrading with higher-efficiency and higher-power-factor lighting equipment can also free up valuable electrical capacity.



Applications

They are two types of applications, the indoor and outdoor series. For the indoor series installing in living room, bedroom or any places in indoor is best recommended. As for the outdoor series, installing at porch, balcony, pergola or whichever is suitable are best recommended.

Indoor Lighting

Spotlight Luminaires | Living Room • Bedroom • Kitchen • Toilet



TUTTLINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TTG01-0309	9	(W 115 x L 115 x H 86)
LSSC-TTG01-0412	15	(W 145 x L 145 x H 102)
LSSC-TTG01-0525	25	(W 170 x L 170 x H 115)
LSSC-TTG01-0640	40	(W 190 x L 190 x H 132)



TUTTLINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TTG02-0309	18	(W 210 x L 115 x H 86)
LSSC-TTG02-0415	30	(W 265 x L 145 x H 102)



TUBINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TBG01-0309	9	(W 110 x L 110 x H 73)
LSSC-TBG01-0415	15	(W 140 x L 140 x H 86)
LSSC-TBG01-0525	25	(W 160 x L 160 x H 97)
LSSC-TBG01-0640	40	(W 180 x L 180 x H 112)



TUBINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TBG02-0309	18	(W 205 x L 110 x H 73)
LSSC-TBG02-0412	30	(W 260 x L 140 x H 86)

Indoor Lighting

Spotlight Luminaires | Living Room • Bedroom • Kitchen • Toilet



GÖPPINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TBG01-0309	9	(φ108 x H 52)
LSSC-TBG01-0415	15	(φ142 x H 65)
LSSC-TBG01-0525	25	(φ158 x H 75)
LSSC-TBG01-0640	40	(φ185 x H 88)
LSSC-TBG01-0860	60	(φ226 x H 108)



BREISGAU

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-TBG01-0309	9	(W 140 x L 140 x H 68)
LSSC-TBG01-0415	15	(W 160 x L 160 x H 88)
LSSC-TBG01-0525	25	(W 140 x L 180 x H 96)
LSSC-TBG01-0640	40	(W 200 x L 200 x H 111)

Indoor Lighting

Downlight Luminaires | Living Room • Bedroom • Kitchen • Toilet



KONSTANZ

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-KST01-0412	12	(W 140 x L 140 x H 57)
LSSC-KST01-0620	20	(W 180 x L 180 x H 67)
LSSC-KST01-0830	30	(W 220 x L 220 x H 67)



LÖRRACH

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Code Number	Power (W)	Dimensions (MM)
LSSC-LRH02-0412	12	(φ 100 x H 63)
LSSC-LRH02-0620	20	(φ 145 x H 63)
LSSC-LRH02-0830	30	(φ 195 x H 63)



BODENSEE

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-BDS01-0305	5	(W 100 x L 100 x H 52)
LSSC-TBG01-0409	9	(W 130 x L 130 x H 52)
LSSC-TBG01-0515	15	(W 160 x L 160 x H 52)
LSSC-TBG01-0618	18	(W 185 x L 185 x H 53)
LSSC-TBG01-0824	24	(W 230 x L 230 x H 53)



BÖBLINGEN

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K,4000K,5000K,6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White	
Code Number	Power (W)	Dimensions (MM)
LSSC-BBG01-0305	5	(W 100 x L 100 x H 52)
LSSC-BBG01-0409	9	(W 140 x L 140 x H 52)
LSSC-BBG01-0515	15	(W 150 x L 150 x H 52)
LSSC-BBG01-0618	18	(W 170 x L 170 x H 52)
LSSC-BBG01-0824	24	(W 210 x L 210 x H 52)

Indoor Lighting

Downlight Luminaires | Living Room • Bedroom • Kitchen • Toilet



BIBERACH

Indoor lighting

Input voltage (V)	100-240VAC, 50/60HZ	
Power Factor (PF)	≥0.9	
CRI	≥80	
CCT	2700K, 4000K, 5000K, 6500K	
Material	Aluminum + Cold Forged	
Colour	Pearl White + Black Star	
Code Number	Power (W)	Dimensions (MM)
LSSC-BBR01-0305	5	(φ 108 x H 51)
LSSC-BBR01-0409	9	(φ 137 x H 51)
LSSC-BBR01-0515	15	(φ 157 x H 51)
LSSC-BBR01-0618	18	(φ 195 x H 51)
LSSC-BBR01-0824	24	(φ 229 x H 51)